

ULTRAVIOLET SYSTEMS



BETTERLIFE™ SYSTEM 2 SOFTENING RESIN WITH UV STERILIZATION



Safe Water Technologies' patented BetterLife system is the flagship of the SWT product line. There is no other water treatment system available for the whole house that compares. A computerized controller meters the water flow for optimal cost savings. The ion exchange portion of the system utilizes ProSoft™ Resin as the primary layer. These cation exchange units are designed to remove calcium and magnesium (hardness) and a host of other cations from the water stream. The ultraviolet design adds bacteriological safeguards to your water supply.

BetterLife System 2 Includes:

- ProSoft Premium cation exchange resin
- 10 gpm stainless steel ultraviolet chamber
- 30,000 µw sec/cm² UV dosage
- Computer controlled and metered valve
- Chlorastick™ pipe sanitizing kit
- Corrosion-free system

BetterLife System 2 with UV Sterilization

Part Number	Tank Size Inches	Softening Capacity		Service Flow Rate		Backwash 50% Exp. @ 50°F	Standard Connection Size *
		10 lb Salt/Cu.Ft.	15 lb Salt/Cu.Ft.	Standard	Peak		
BL2L-100	10 x 47	29,000 gr.	33,000 gr.	5 gpm	10 gpm	2.0 gpm	3/4" Copper Swet
BL2L-175	12 x 48	51,000 gr.	57,000 gr.	8 gpm	10 gpm	3.7 gpm	3/4" Copper Swet

High Sediment & Rural Applications (System Includes Option BLS-R)

BL2L-100R	10 x 47	29,000 gr.	33,000 gr.	5 gpm	10 gpm	2.0 gpm	3/4" Copper Swet
BL2L-175R	12 x 48	51,000 gr.	57,000 gr.	8 gpm	10 gpm	3.7 gpm	3/4" Copper Swet

International voltages available at additional cost.

* 1 inch connections and threaded adapters available on request.

Options and Upgrades

Part Number	Description
BLS-R	10 Micron Pleated Prefilter with 20 inch Clear Bypass Housing (Highly Recommended For Rural Applications)
BLS-C	Whole House Carbon Cartridge Assembly Includes 20 inch Big Blue Housing, Big Blue GAC Cartridge, and Bracket
BLS-P	1 Micron Absolute Postfilter Assembly for Cryptosporidium and Giardia Cyst Removal
BLS-E	Instant Start Electronic Ballast (Autodetects 50/60 Hz)
BLS-A	Controller Board with Lamp Status LED, Audible Alarm, and Solenoid Valve Hookup
BLS-S	Solenoid Valve Assembly — Requires Upgraded Electronic Ballast

Resin substitutions are available: Nitrate, Tannin, etc.

WARNING AND DISCLAIMER: Ultraviolet treatment, chlorinating, or any other form of sanitation of contaminated water, are never 100% guaranteed for bacteriological-free water, but are EPA approved methods of water sanitation which add greatly to protection against waterborne pathogens. Proper ultraviolet sterilization is an instantaneous process which destroys 99.97% of pathogens and leaves no UV residual in the water. Periodic monitoring of the water supply and of the downstream piping system sanitation is recommended to help guard against downstream contamination or accidentally contaminated water bypass. Ultraviolet sterilization and/or chlorine, is **not recommended and should not be used** for cyst treatment.

ULTRAVIOLET SYSTEMS



BETTERLIFE™ SYSTEM 2 SOFTENING RESIN WITH UV STERILIZATION

Replacement Parts

Part Number	Description
IL10001	Ultraviolet Lamp
CF73210	10 Micron Pleated Sediment Cartridge (2.5 x 20 inch Prefilter)
AH-PPBB201	1 Micron Absolute Pleated Cartridge for Cryptosporidium and Giardia Cysts (4.5 x 20 inch Postfilter)
APS-CSRA	Replacement Chlorastick™ Pipe Sanitizing Module
IL30001	Quartz Sleeve
UL-118RS	Red Silicone O-Ring for Quartz Sleeve
EC-LL68	Safety Spring
MA-15515343	Granular Activated Carbon Cartridge for Big Blue Housing (4.5 x 20 inch)



Chlorastick Pipe Sanitizing Kit (Included)

Contains:

- Lever Action, Brass Ball Valves
- Quick Release, Union Fittings with O-Ring Seals
- Disposable Chlorine Chamber
- Sch 80 PVC Replacement Pipe



Prefilter Assembly (Optional)

Contains:

- 20 inch Clear Housing with Built-in Bypass and 3/4 inch NPT
- 2.5 x 20 inch Pleated Cartridge with 10 Micron Filtration
- Spanner Wrench
- Wall Mount Bracket



Postfilter Assembly (Optional)

Contains:

- 20 inch Big Blue Sump with Pressure Relief and 3/4 inch NPT
- 4.5 x 20 inch Pleated Cartridge with 1 Micron Filtration for Giardia Cysts
- Spanner Wrench
- Wall Mount Bracket

Additional Specifications — BetterLife System 2

Shipping Dimensions (Inches):

BL2L-100: 17 x 13 x 58 @ 95 lb / Brine Tank: 18 x 16 x 37 @ 30 lb

BL2L-175: 17 x 13 x 59 @ 145 lb / Brine Tank: 18 x 16 x 37 @ 30 lb

Operating Pressure: 20 to 125 psi

Operating Temperature: 36 to 120°F (2 to 48.9°C)