

COMMERCIAL RO SYSTEMS




BRACKISH WATER, RIVER INTAKE AND SEAWATER INTRUSION SYSTEMS (NOMINAL 6,500 TDS DESIGN)

Standard Features

- Energy efficient, high flow membranes
- 5 micron sediment pre-filter
- Allen-Bradley programmable controller
- Liquid level float with auto shut-off
- Auto-flush system
- Pre- and post-filter, feed, concentrate, and product water pressure gauges
- Visual inline flow meters
- Low pressure feed water switch
- Victaulic style 304 stainless steel housing connections
- Low pressure alarm capable
- Motor starter with safety disconnect

Optional Features

- 2 m³/d field portable system with gas or diesel powered generator
- Digital permeate TDS meter
- Automatic antiscalant dosing system
- Automatic or manual pH control dosing system
- Ethernet communication upgrade for the controller
- Digital permeate and concentrate flow meters with low level alarms
- Digital supply and concentrate pressure gauges with high level alarms
- Clean-in-place membrane maintenance station
- System shutdown during permeate flush
- Stainless steel wetted parts for liquid end of pump
- Step-down transformer from 3 phase to single phase
- Available in all international voltages



Operating Parameters

Operating Pressure	250 to 450 psi
Min. Supply Pressure	15 psi
Max. Temperature	113°F (45°C)
Nominal TDS	6,500 ppm
Max. Inlet Free Chlorine	< 0.1 ppm

Specifications

Membrane Housings	High pressure, fiberglass reinforced plastic membrane housings
Frame	Structural fiberglass and aluminum
Controller Power Requirements	120V/60Hz/1Ph
Motor Power Requirements	230-460V/60Hz/3Ph
Pumps (HTS-2 to HTS-20)	Rotary vane pump with brass head and Buna diaphragm
(HTS-28 to HTS-82)	Multi-stage centrifugal pump with stainless steel wetted parts and Viton seals

COMMERCIAL RO SYSTEMS



BRACKISH WATER, RIVER INTAKE AND SEAWATER INTRUSION SYSTEMS

	HTS-2-B	HTS-4-B	HTS-8-B	HTS-12-B	HTS-20-B	HTS-28-B	HTS-38-B	HTS-57-B	HTS-82-B
Actual Permeate (m ³ /d / gpd)	2 / 528	4 / 1056	8 / 2114	12 / 3170	20 / 5284	28.4 / 7503	38 / 10,040	57 / 15,060	82 / 21,664
Nominal Size (m ³ /d / gpd)	4.5 / 1200	4.5 / 1200	9.1 / 2400	18.2 / 4800	27.3 / 7200	36.3 / 9600	40.9 / 10800	67 / 17,700	89.3 / 23,600
Recovery	10 - 50%	10 - 50%	10 - 50%	10 - 50%	45 - 60%	45 - 60%	45 - 60%	45 - 60%	50 - 60%
Concentration Rate (gpm)	3.1	3.2	3.1	2.0	3.0	3.1	8.5	12.3	12.1
Recycle Rate (gpm)	0.0	0.0	0.0	1.0	0.0	0.0	0.0	0.0	0.0
Supply Rate (gpm)	3.5	4.0	4.6	4.2	6.7	8.3	15.5	22.7	27.1
RO Pump Design Flow (gpm)	3.5	4.0	4.6	5.2	6.7	8.3	15.5	22.7	27.1
RO Pump Design Pressure (psi)	450.0	679.0	800.0	850.0	880.0	980.0	865.0	930.0	1000.0
RO Motor HP (60 Hz)	2.0	2.0	5.0	5.0	5.0	7.5	15.0	20.0	25.0
RO Motor kWh @ Flow	1.20	2.07	2.80	3.36	4.49	6.19	10.20	20.00	24.80
CIP Pump Design Flow (gpm)	10	10	10	10	20	20	20	30	30
CIP Pump Design Pressure (psi)	60	60	60	60	60	60	60	60	60
CIP Motor HP (60 Hz)	1	1	1	1	2	2	2	3	3
CIP Motor kWh @ Flow	0.91	0.91	0.91	0.91	1.83	1.83	1.83	2.74	2.74
Chemical Pretreatment	Optional	Optional	Required	Required	Required	Required	Required	Required	Required
Membrane Elements									
Diameter (in / cm)	4 / 10.16	4 / 10.16	4 / 10.16	4 / 10.16	4 / 10.16	4 / 10.16	4 / 10.16	8 / 20.32	8 / 20.32
Number	1	1	2	2	2	2	3	1	1
Array (Pressure Vessels)	1-0	1-0	1-1	1-1	1-1	1-1	2-1	1-0	1-0
Connections NPS & DN									
Inlet (in / mm)	1/2 - 15	1/2 - 15	1/2 - 15	1/2 - 15	3/4 - 20	3/4 - 20	1 - 25	1 - 25	1 - 25
Permeate (in / mm)	1/2 - 15	1/2 - 15	1/2 - 15	1/2 - 15	1/2 - 15	1/2 - 15	3/4 - 20	1 - 25	1 - 25
Concentration (in / mm)	1/2 - 15	1/2 - 15	1/2 - 15	1/2 - 15	1/2 - 15	1/2 - 15	1/2 - 15	3/4 - 20	3/4 - 20
Estimated Footprint									
Height (in / cm)	30 / 76	30 / 76	30 / 76	30 / 76	36 / 91	36 / 91	60 / 152	60 / 152	60 / 152
Width (in / cm)	48 / 122	48 / 122	48 / 122	92 / 233.7	132 / 335.3	172 / 436.9	132 / 335.3	132 / 335.3	172 / 436.9
Depth (in / cm)	24 / 61	24 / 61	24 / 61	24 / 61	24 / 61	24 / 61	30 / 76	30 / 76	30 / 76
Estimated Weight									
Shipping (lb / kg)	195 / 88.45	195 / 88.45	220 / 99.8	285 / 130	330 / 150	420 / 191	455 / 206.4	498 / 226	624 / 284
Installed (lb / kg)	204 / 92.5	204 / 92.5	239 / 108.4	239 / 108.4	297 / 134.7	321 / 145.6	455 / 206.4	526 / 238.6	601 / 272.6

SAFE WATER TECHNOLOGIES, INC.
 996 BLUFF CITY BOULEVARD, ELGIN, IL 60120 USA
 TELEPHONE 847 888 6900 • FACSIMILE 847 888 6924
 E MAIL: info@swtwater.com • WEB SITE: www.swtwater.com



FORM 1287
 EFFECTIVE
 JULY 2003