

FILTER HOUSINGS



JUMBO STAINLESS STEEL FILTER HOUSINGS

SWT's Jumbo Stainless Steel Filter Housings are designed for food industry and high temperature applications with flow rates up to 30 gpm. Available for 10 or 20 inch Big Blue® filter cartridges, these high flow housings feature 304 stainless steel construction with food grade EPDM seals, 1 inch FNPT connections, and 1/4 inch NPT drain port.



FEATURES

- Eliminates risk of leaks and failures associated with plastic filter housings
- Solid metal construction in premium grade AISI 304 stainless steel
- Food-grade EPDM seals are standard (Viton seals are optional)
- Suitable for use with potable water and food products
- Accepts standard cartridges: 4-1/2 inch OD x 10 or 20 inch nominal length
- Spring-loaded seal plate in sump assures sealing with variable-length cartridges
- Installation kit includes mounting bracket and ring nut disassembly tool
- Sump features a 1/4 inch NPT drain plug

ADDITIONAL INFORMATION

Pressure: 150 psi (1.03 MPa) maximum

Temperature: 210°F (99°C) maximum

Cartridge Type: Double open ended style

Extras: Viton seals

Part Number	Cartridges		Flow Rate**		Connection Size		Dimensions	
	Length Inches*	Diameter Inches	GPM	LPM	Pipe NPT Inches	Drain NPT Inches	Height Inches	OD Inches
YH22501BB-S	10	4-1/2	12	45	1	1/4	15	5
YH22502BB-S	20	4-1/2	12	45	1	1/4	25	5
YH25501BB-S-1.5	10	4-1/2	28	106	1.5	1/4	15	5
YH25501BB-S-2.0	10	4-1/2	48	181	2.0	1/4	15	5
YH25502BB-S-1.5	20	4-1/2	28	106	1.5	1/4	25	5
YH25502BB-S-2.0	20	4-1/2	48	181	2.0	1/4	25	5

* Equivalent lengths accepted: 10 inch = (9.75 to 10 inch); 20 inch = (19.5 to 20 inch)

** Flow rates are for guidelines only. Actual flow rates are based on fluid, viscosity, cartridge type, micron ratings, and other factors.

Big Blue® is a registered trademark of Pentair Residential Filtration, LLC.